

Tennessee Storm Water Multi-Sector  
General Permit for Industrial Activities (TMSP)  
**Sector R**

**R      Sector R - Storm Water Discharges Associated With Industrial Activity From Ship  
and Boat Building or Repairing Yards**

**1.   Discharges Covered Under This Section**

The requirements listed under this section shall apply to storm water discharges associated with industrial activity from a facility engaged in manufacturing the following products and generally described by the SIC codes shown below:

SIC Code	Sector R: Ship or Boat Building and Repair Yards	Sampling Required?	Table Number
3731	Ship Building and Repairing	No	--
3732	Boat Building and Repairing	No	--

When an industrial facility, described by the above coverage provisions of this section, has industrial activities being conducted onsite that meet the description(s) of industrial activities in another section(s), that industrial facility shall comply with any and all applicable monitoring and pollution prevention plan requirements of the other section(s) in addition to all applicable requirements in this section. The monitoring and pollution prevention plan terms and conditions of this multi-sector permit are additive for industrial activities being conducted at the same industrial facility (co-located industrial activities). The operator of the facility shall determine which other monitoring and pollution prevention plan section(s) of this permit (if any) are applicable to the facility.

**2.   Special Conditions**

Prohibition of Non-storm Water Discharges. In addition to the prohibitions listed in Part III.A of the permit, this section specifically prohibits non-storm water discharges of wastewaters, such as bilge and ballast water, pressure wash water, sanitary wastes, and cooling water originating from vessels, are not authorized by this permit. The operators of such discharges must obtain coverage under a separate NPDES permit if discharged to waters of the State or through a municipal separate storm sewer system.

**3.   Storm Water Pollution Prevention Plan Requirements**

Contents of Plan. The plan shall include, at a minimum, the following items:

Pollution Prevention Team. Each plan shall identify a specific individual or individuals within the facility organization as members of a storm water Pollution Prevention Team that are responsible for developing the storm water pollution prevention plan and assisting the facility or plant manager in its implementation, maintenance, and revision. The plan shall clearly identify the responsibilities of each team member. The activities and responsibilities of the team shall address all aspects of the facility's storm water pollution prevention plan.

Description of Potential Pollutant Sources. Each plan shall provide a description of potential sources which may reasonably be expected to add significant amounts of pollutants to storm water discharges or which may result in the discharge of pollutants during dry weather from separate storm sewers draining the facility. Each plan shall identify all activities and significant materials which may potentially be significant pollutant sources. Each plan shall include, at a minimum:

**Drainage.** A site map indicating the location of the outfalls and the types of discharges contained in the drainage areas of the outfalls, an outline of the portions of the drainage area of each storm water outfall that are within the facility boundaries, each existing structural control measure to reduce pollutants in storm water runoff, surface water bodies, locations where significant materials are exposed to precipitation, locations where major spills or leaks identified under Part XI.R.3.a.(2)(c) (Spills and Leaks) of this section have occurred, and the locations of the following activities where such activities are exposed to precipitation: fueling, engine maintenance and repair, vessel maintenance and repair, pressure washing, painting, sanding, blasting, welding, metal fabrication, loading/unloading areas, locations used for the treatment, storage or disposal of wastes; liquid storage tanks, liquid storage areas (i.e., paint, solvents, resins), and material storage areas (i.e., blasting media, aluminum, steel, scrap iron).

For each area of the facility that generates storm water discharges associated with industrial activity with a reasonable potential for containing significant amounts of pollutants, a prediction of the direction of flow, and an identification of the types of pollutants which are likely to be present in storm water discharges associated with industrial activity. Factors to consider include the toxicity of a chemical; quantity of chemicals used, produced or discharged; the likelihood of contact with storm water; and history of significant leaks or spills of toxic or hazardous pollutants. Flows with a significant potential for causing erosion shall be identified.

**Inventory of Exposed Materials**—An inventory of the types of materials handled at the site that potentially may be exposed to precipitation. Such inventory shall include a narrative description of significant materials that have been handled, treated, stored or disposed in a manner to allow exposure to storm water between the time of 3 years prior to the date of the submission of a Notice of Intent (NOI) to be covered under this permit and the present; method and location of onsite storage or disposal; materials management practices employed to minimize contact of materials with storm water runoff between the time of 3 years prior to the date of the submission of a Notice of Intent (NOI) to be covered under this permit and the present; the location and a description of existing structural and nonstructural control measures to reduce pollutants in storm water runoff; and a description of any treatment the storm water receives.

**Spills and Leaks**—A list of significant spills and significant leaks of toxic or hazardous pollutants that occurred at areas that are exposed to precipitation or that otherwise drain to a storm water conveyance at the facility after the date of 3 years prior to the date of the submission of a Notice of Intent (NOI) to be covered under this permit. Such list shall be updated as appropriate during the term of the permit.

**Sampling Data**—A summary of existing discharge sampling data describing pollutants in storm water discharges from the facility, including a summary of sampling data collected during the term of this permit.

**Risk Identification and Summary of Potential Pollutant Sources**—A narrative description of the potential pollutant sources from the following activities if applicable: loading and unloading operations; outdoor storage activities; outdoor manufacturing or processing activities (i.e., welding, metal fabricating); significant dust or particulate generating processes (i.e., abrasive blasting, sanding, painting); loading/unloading areas; and onsite waste disposal practices. The description shall specifically list any significant potential source of pollutants at the site and for each potential source, any pollutant or pollutant parameter (e.g., biochemical oxygen demand, etc.) of concern shall be identified.

Tennessee Storm Water Multi-Sector  
General Permit for Industrial Activities (TMSP)  
**Sector R**

**Measures and Controls.** Each facility covered by this permit shall develop a description of storm water management controls appropriate for the facility, and implement such controls. The appropriateness and priorities of controls in a plan shall reflect identified potential sources of pollutants at the facility. The description of storm water management controls shall address the following minimum components, including a schedule for implementing such controls:

**Good Housekeeping**—Good housekeeping requires the maintenance of areas which may contribute pollutants to storm water discharges in a clean, orderly manner. The following areas must be specifically addressed, when applicable at a facility:

**Pressure Washing Area**—When pressure washing is used to remove marine growth from vessels, the discharge water must be permitted as a process wastewater by an NPDES permit.

**Blasting and Painting Areas**—The facility must consider containing all blasting and painting activities to prevent abrasives, paint chips, and overspray from reaching the receiving water or the storm sewer system. The plan must describe measures taken at the facility to prevent or minimize the discharge of spent abrasive, paint chips, and paint into the receiving waterbody and storm sewer system. The facility may consider hanging plastic barriers or tarpaulins during blasting or painting operations to contain debris. Where required, a schedule for cleaning storm systems to remove deposits of abrasive blasting debris and paint chips should be addressed within the plan. The plan should include any standard operating practices with regard to blasting and painting activities. Practices may include the prohibition of performing uncontained blasting and painting over open water or blasting and painting during windy conditions which can render containment ineffective.

**Material Storage Areas**—All stored and containerized materials (fuels, paints, solvents, waste oil, antifreeze, batteries) must be stored in a protected, secure location away from drains and plainly labeled. The plan must describe measures that prevent or minimize contamination of the storm water runoff from such storage areas. The facility must specify which materials are stored indoors and consider containment or enclosure for materials that are stored outdoors. Above ground storage tanks, drums, and barrels permanently stored outside must be delineated on the site map with a description of the containment measures in place to prevent leaks and spills. The facility must consider implementing an inventory control plan to prevent excessive purchasing, storage, and handling of potentially hazardous materials. Those facilities where abrasive blasting is performed must specifically include a discussion on the storage and disposal of spent abrasive materials generated at the facility.

**Engine Maintenance and Repair Areas**—The plan must describe measures that prevent or minimize contamination of the storm water runoff from all areas used for engine maintenance and repair. The facility must consider performing all maintenance activities indoors, maintaining an organized inventory of materials used in the shop, draining all parts of fluids prior to disposal, prohibiting wet clean up practice where the practice would result in the exposure of pollutants to storm water, using dry cleanup methods, and/or collecting the storm water runoff from the maintenance area and providing treatment or recycling.

**Material Handling Areas**—The plan must describe measures that prevent or minimize contamination of the storm water runoff from material handling operations and areas (i.e., fueling, paint & solvent mixing, disposal of process wastewater streams from vessels). The facility must consider covering fueling areas; using spill and overflow protection; mixing paints and solvents in a designated area, preferably indoors or under a shed; and minimizing runoff of storm water to material handling areas.

Where applicable, the plan must address the replacement or repair of leaking connections, valves, pipes, hoses, and soil chutes carrying wastewater from vessels.

**Drydock Activities**—The plan must address the routine maintenance and cleaning of the drydock to minimize the potential for pollutants in the storm water runoff. The plan must describe the procedures for cleaning the accessible areas of the drydock prior to flooding and final cleanup after the vessel is removed and the dock is raised. Cleanup procedures for oil, grease, or fuel spills occurring on the drydock must also be included within the plan. The facility must consider items such as sweeping rather than hosing off debris and spent blasting material from the accessible areas of the drydock prior to flooding and having absorbent materials and oil containment booms readily available to contain and cleanup any spills.

**General Yard Area**—The plan must include a schedule for routine yard maintenance and cleanup. Scrap metal, wood, plastic, miscellaneous trash, paper, glass, industrial scrap, insulation, welding rods, packaging, etc., must be routinely removed from the general yard area. The facility must consider such measures as providing covered trash receptacles in each yard, on each pier, and on board each vessel being repaired.

**Preventive Maintenance**—A preventive maintenance program shall involve timely inspection and maintenance of storm water management devices (e.g., cleaning oil/water separators, sediment traps to ensure that spent abrasives, paint chips, and solids will be intercepted and retained prior to entering the storm drainage system) as well as inspecting and testing facility equipment and systems to uncover conditions that could cause breakdowns or failures resulting in discharges of pollutants to surface waters, and ensuring appropriate maintenance of such equipment and systems.

**Spill Prevention and Response Procedures**—Areas where potential spills which can contribute pollutants to storm water discharges can occur, and their accompanying drainage points shall be identified clearly in the storm water pollution prevention plan. Where appropriate, specifying material handling procedures, storage requirements, and use of equipment such as diversion valves in the plan should be considered. Procedures for cleaning up spills shall be identified in the plan and made available to the appropriate personnel. The necessary equipment to implement a clean up should be available to personnel.

**Inspections**—Qualified facility personnel shall be identified to inspect designated equipment and areas of the facility on a monthly basis. The following areas shall be included in all inspections: pressure washing area; blasting, sanding, and painting areas; material storage areas; engine maintenance and repair areas; material handling areas; drydock area; and general yard area. A set of tracking or follow-up procedures shall be used to ensure that appropriate actions are taken in response to the inspections. Records of inspections shall be maintained.

**Employee Training**—Employee training programs shall inform personnel responsible for implementing activities identified in the storm water pollution prevention plan or otherwise responsible for storm water management at all levels of responsibility of the components and goals of the storm water pollution prevention plan. The pollution prevention plan shall identify how often training will take place, but in all cases training must be held at least annually (once per calendar year). Employee training must, at a minimum, address the following areas when applicable to a facility: used oil management; spent solvent management; proper disposal of spent abrasives; proper disposal of vessel wastewaters, spill prevention and control; fueling procedures; general good housekeeping practices; proper painting and

Tennessee Storm Water Multi-Sector  
General Permit for Industrial Activities (TMSP)  
**Sector R**

blasting procedures; and used battery management. Employees, independent contractors, and customers must be informed about BMPs and be required to perform in accordance with these practices. The facility should consider posting easy to read descriptions or graphic depictions of BMPs and emergency phone numbers in the work areas.

**Recordkeeping and Internal Reporting Procedures**—A description of incidents (such as spills, or other discharges), along with other information describing the quality and quantity of storm water discharges shall be included in the plan required under this part. Inspections and maintenance activities shall be documented and records of such activities shall be incorporated into the plan.

#### Non-storm Water Discharges

The plan shall include a certification that the discharge has been tested or evaluated for the presence of non-storm water discharges. The certification shall include the identification of potential significant sources of non-storm water at the site, a description of the results of any test and/or evaluation for the presence of non-storm water discharges, the evaluation criteria or testing method used, the date of any testing and/or evaluation, and the onsite drainage points that were directly observed during the test. Certifications shall be signed in accordance with Part VII.G. of this permit. Such certification may not be feasible if the facility operating the storm water discharge associated with industrial activity does not have access to an outfall, manhole, or other point of access to the ultimate conduit which receives the discharge. In such cases, the source identification section of the storm water pollution prevention plan shall indicate why the certification required by this part was not feasible, along with the identification of potential significant sources of non-storm water at the site. A discharger that is unable to provide the certification required by this paragraph must notify the Division of Water Pollution Control in accordance with paragraph “Failure to Certify” (below).

Sources of non-storm water that are combined with storm water discharges associated with industrial activity must be identified in the plan. The plan shall identify and ensure the implementation of appropriate pollution prevention measures for the non-storm water component(s) of the discharge. Any non-storm water discharges that are not permitted under an individual NPDES permit should be brought to the attention of the Division’s local Environmental Assistance Center (see list of EACs on page 15).

**Failure to Certify**—Any facility that is unable to provide the certification required (testing for non-storm water discharges), must notify the Division of Water Pollution Control by not later than 180 days after submitting an NOI to be covered by this permit. If the failure to certify is caused by the inability to perform adequate tests or evaluations, such notification shall describe: the procedure of any test conducted for the presence of non-storm water discharges; the results of such test or other relevant observations; potential sources of non-storm water discharges to the storm sewer; and why adequate tests for such storm sewers were not feasible. Non-storm water discharges to waters of the State which are not authorized by an NPDES permit are unlawful, and must be terminated.

**Sediment and Erosion Control**—The plan shall identify areas which, due to topography, activities, or other factors, have a high potential for significant soil erosion, and identify structural, vegetative, and/or stabilization measures to be used to limit erosion.

**Management of Runoff**—The plan shall contain a narrative consideration of the appropriateness of traditional storm water management practices (practices other than those which control the generation or source(s) of pollutants) used to divert, infiltrate, reuse, or otherwise manage storm water runoff in a

manner that reduces pollutants in storm water discharges from the site. The plan shall provide that measures that the permittee determines to be reasonable and appropriate shall be implemented and maintained. The potential of various sources at the facility to contribute pollutants to storm water discharges associated with industrial activity [see paragraph XI.R.3.a.(2) of this section (Description of Potential Pollutant Sources)] shall be considered when determining reasonable and appropriate measures. Appropriate measures or other equivalent measures may include: vegetative swales and practices, reuse of collected storm water (such as for a process or as an irrigation source), inlet controls (such as oil/water separators), snow management activities, infiltration devices, and wet detention/retention devices.

**Comprehensive Site Compliance Evaluation.** Qualified personnel shall conduct site compliance evaluations at appropriate intervals specified in the plan, but in no case less than once a year. Such evaluations shall provide:

Areas contributing to a storm water discharge associated with industrial activity including, but not limited to, pressure washing area, blasting and sanding areas, painting areas, material storage areas, engine maintenance and repair areas, material handling areas, and drydock area, shall be visually inspected for evidence of, or the potential for, pollutants entering the drainage system. Measures to reduce pollutant loadings shall be evaluated to determine whether they are adequate and properly implemented in accordance with the terms of the permit or whether additional control measures are needed. Structural storm water management measures, sediment and erosion control measures, and other structural pollution prevention measures identified in the plan shall be observed to ensure that they are operating correctly. A visual inspection of equipment needed to implement the plan, such as spill response equipment, shall be made.

Based on the results of the evaluation, the description of potential pollutant sources identified in the plan in accordance with paragraph XI.R.3.a.(2) of this section (Description of Potential Pollutant Sources) and pollution prevention measures and controls identified in the plan in accordance with paragraph XI.R.3.a.(3) of this section (Measures and Controls) shall be revised as appropriate within 2 weeks of such evaluation and shall provide for implementation of any changes to the plan in a timely manner, but in no case more than 12 weeks after the evaluation.

A report summarizing the scope of the evaluation, personnel making the evaluation, the date(s) of the evaluation, major observations relating to the implementation of the storm water pollution prevention plan, and actions taken in accordance with paragraph XI.R.3.a.(4)(b) (above) of the permit shall be made and retained as part of the storm water pollution prevention plan for at least 3 years from the date of the evaluation. The report shall identify any incidents of noncompliance. Where a report does not identify any incidents of noncompliance, the report shall contain a certification that the facility is in compliance with the storm water pollution prevention plan and this permit. The report shall be signed in accordance with Part VII.G. (Signatory Requirements) of this permit.

Where compliance evaluation schedules overlap with inspections required under 3.a.(3)(d), the compliance evaluation may be conducted in place of one such inspection.

#### 4. Numeric Effluent Limitations

There are no additional numeric effluent limitations beyond those described in Part V.B of this permit.

Tennessee Storm Water Multi-Sector  
General Permit for Industrial Activities (TMSP)  
**Sector R**

5. Monitoring and Reporting Requirements

Quarterly Visual Examination of Storm Water Quality. Facilities shall perform and document a visual examination of a representative storm water discharge associated with industrial activity from each outfall except discharges exempted below. The examination must be made at least once in each designated period [described in (1) below] during daylight hours unless there is insufficient rainfall or snow melt to produce a runoff event.

Examinations shall be conducted in each of the following periods for the purposes of visually inspecting storm water quality associated with storm water runoff or snowmelt: January through March; April through June; July through September; October through December.

Examinations shall be made of samples collected within the first 30 minutes (or as soon thereafter as practical, but not to exceed 1 hour) of when the runoff or snowmelt begins discharging. The examinations shall document observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of storm water pollution. The examination must be conducted in a well lit area. No analytical tests are required to be performed on the samples. All such samples shall be collected from the discharge resulting from a storm event that is greater than 0.1 inches in magnitude and that occurs at least 72 hours from the previously measurable (greater than 0.1 inch rainfall) storm event. Where practicable, the same individual should carry out the collection and examination of discharges for entire permit term.

Visual examination reports must be maintained onsite in the pollution prevention plan or with other compliance records. The report shall include the examination date and time, examination personnel, the nature of the discharge (i.e., runoff or snow melt), visual quality of the storm water discharge (including observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of storm water pollution), and probable sources of any observed storm water contamination.

When a facility has two or more outfalls that, based on a consideration of industrial activity, significant materials, and management practices and activities within the area drained by the outfall, the permittee reasonably believes discharge substantially identical effluents, the permittee may collect a sample of effluent of one of such outfalls and report that the examination data also applies to the substantially identical outfall(s) provided that the permittee includes in the storm water pollution prevention plan a description of the location of the outfalls and explains in detail why the outfalls are expected to discharge substantially identical effluents. In addition, for each outfall that the permittee believes is representative, an estimate of the size of the drainage area (in square feet) and an estimate of the runoff coefficient of the drainage area [e.g., low (under 40 percent), medium (40 to 65 percent), or high (above 65 percent)] shall be provided in the plan.

When a discharger is unable to collect samples over the course of the monitoring period as a result of adverse climatic conditions, the discharger must document the reason for not performing the visual examination. Adverse weather conditions which may prohibit the collection of samples include weather conditions that create dangerous conditions for personnel (such as local flooding, high winds, hurricane, tornadoes, electrical storms, etc.) or otherwise make the collection of a sample impracticable (drought, extended frozen conditions, etc.).

When a discharger is unable to conduct visual storm water examinations at an inactive and unstaffed site, the operator of the facility may exercise a waiver of the monitoring requirement as long as the facility remains inactive and unstaffed. The facility must maintain a certification with the pollution prevention plan stating that the site is inactive and unstaffed so that performing visual examinations during a qualifying event is not feasible.